

Bennu Hydraulic Mast-Climbing Scaffolding Platform APU Series #3

APU - Automatic Power Unit Main Features

Platform dimensions: 24 ft. x 7 ft.

Setup length: 1 unit = 24 ft. to 64 ft.

2 units = 48 ft. to 138 ft.

Collapsed height: 55 inches

Elevation height: 0 - 30 ft. = Free standing

30 ft. - 100 ft. = Wall tie every 15 ft. 300 ft. maximum height (see manual)

Shipping weight: 9,300 lbs with standard accessories

Load capacity: High speed - 12,000 lbs Low speed - 20,000 lbs

Elevation speeds: High speed = up to 10 ft. / minute

Low speed = up to 5 ft. / minute 13HP GX 390K1 Honda engine,

electric start, oil alert

and guard rails

6. (1) ladder access door

7. (1) power pack access door

Details

Engine:

Guard rails: Accessories:

1. (2) 48" Adj. guard rails 5. (1) foldable access ladder with 2. (2) door guard rails built-in rest-platform

2. (2) door guard rails3. (2) sliding doors

4. (2) mast toe guards

4. (2) mast toe guards
(2) mason guard rails
(not shown)

Outriggers:

8. (7) 8 ft. outriggers

Base:
9. (2) Independent bases with starter 40" mast sections

11. (2) stabilizer arms with jacks and standard pads

10. (4) high capacity (160,000 lbs) jacks & horse-shoe pads

12. (2) Transversal stabilizer bars

Lifting system:

13. (1) Powerpack

14. (2) Climbing Wheels

15. (1) Control post

U.S. Patents #8,167,089 B2

APU - Automatic Power Unit Capacity, per unit

CA	PACITY		CANTILEVER CANTILEVER CANTILEVER								
C A N T I L E V E R	LENGTH	0	4	8	12	16	20				
	0	20,000	19,300	18,700	18,000	17,300	16,700				
	4	19,300	18,700	18,000	17,300	16,700	16,000				
	8	18,700	18,000	17,300	16,700	16,000	15,300				
	12	18,000	17,300	16,700	16,000	15,300	14,700				
	16	17,300	16,700	16,000	15,300	14,700	14,000				
	20	16,700	16,000	15,300	14,700	14,000	13,300				

Bennu Parts and Service, Inc. 651 E. Devon Ave.

Elk Grove Village, Illinois 60007 USA

Office: 847-595-8444 | Fax: 847-595-8554 www.bennuparts.com | www.castleandson.com

Office hours: 6:00 AM to 4:30 PM Monday through Friday





C A	CAPACITY		BEARING BEARING BEARING BEARING BEARING															
C A N T I L E V E R	LENGTH	0	12	16	20	24	28	32	36	40	44	48	52	56	60	64	68	72
	0	20,000	19,000	18,700	18,300	18,000	17,700	17,300	17,000	16,700	16,300	16,000	15,700	15,300	15,000	14,700	14,300	14,000
	4	19,300	18,300	18,000	17,700	17,300	17,000	16,700	16,300	16,000	15,700	15,300	15,000	14,700	14,300	14,000	13,700	13,300
	8	18,700	17,700	17,300	17,000	16,700	16,300	16,000	15,700	15,300	15,000	14,700	14,300	14,000	13,700	13,300	13,000	12,700
	12	18,000	17,000	16,700	16,300	16,000	15,700	15,300	15,000	14,700	14,300	14,000	13,700	13,300	13,000	12,700	12,300	12,000
	16	17,300	16,300	16,000	15,700	15,300	15,000	14,700	14,300	14,000	13,700	13,300	13,000	12,700	12,300	12,000	11,700	11,300
	20	16,700	15,700	15,300	15,000	14,700	14,300	14,000	13,700	13,300	13,000	12,700	12,300	12,000	11,700	11,300	11,000	10,600